


**NOTES:**

1. USE WITH TWO LOCKING BOLTS 5/8"-11 NC STAINLESS TYPE 304 STEEL SOCKET HEAD (ALLEN HEAD) BOLTS, 2" LONG. NOTE SLOT DETAIL.
2. MATERIAL IS DUCTILE IRON ASTM A536 GRADE 80-55-06.
3. "OUTFALL TO STREAM DUMP NO POLLUTANTS" IN RAISED LETTERS SHALL BE LOCATED ON GRATE AS SHOWN, BORDER AREA.
4. SHALL CONFORM TO SEC. 7.05 OF THE WSDOT STANDARD SPECIFICATIONS.
5. WELDING IS NOT PERMITTED.
6. USE IN CONTINUOUS SLOPE CONDITIONS ONLY.
7. EDGES SHALL HAVE 0.125" RADIUS, 0.125" CHAMBER OR COMPLETE DEBURRING.
8. USE A THROUGH CURB INLET WITH HERRINGBONE GRATE IN SAG VERTICAL CURVES PER COE STD DTL SD-324.



**CITY OF EDMONDS**  
PUBLIC WORKS  
DEPARTMENT

**VANED GRATE**

APPROVED BY: **R. ENGLISH**

REVISION DATE  
**JANUARY 2018**

STANDARD  
DETAIL  
**SD-323**