



GENERAL NOTES:

1. REFER TO THE 2017 CITY OF EDMONDS STORMWATER ADDENDUM FOR SETBACK AND INFASIBILITY REQUIREMENTS.

NOTES:

1. MAXIMUM OF 700 SQUARE FEET OF ROOF AREA MAY DRAIN TO EACH SPLASHBLOCK.
2. SPLASHBLOCK MAY BE CONCRETE, PLASTIC, OR SIMILAR RIGID MATERIAL.
3. ROCK PAD SHALL CONSIST OF 4" STREAMBED COBBLES PER WSDOT SPEC. 9-03.11(2) OR WASHED DRAIN ROCK CONFORMING TO WSDOT SPEC. 9-03.12(5), GRAVEL BACKFILL FOR DRYWELLS.
4. A VEGETATED FLOW PATH MUST BE PROVIDED IN ACCORDANCE THE 2017 CITY OF EDMONDS STORMWATER ADDENDUM REQUIREMENTS.



CITY OF EDMONDS
PUBLIC WORKS
DEPARTMENT

**TYPICAL DOWNSPOUT
DISPERSION SPLASHBLOCK**

APPROVED BY: R. ENGLISH

REVISION DATE
DECEMBER 2017

STANDARD
DETAIL
SD-633