

**SQUARE METAL POST**


**NOTES:**

**SIGN POST:**

- ① SIGN POST SHALL BE 2"x2" SQUARE STEEL POSTS, MINIMUM 14 GAUGE, WITH 7/16" DIE-PUNCHED KNOCKOUTS ON 1" CENTERS FULL LENGTH FOUR SIDES COMPLYING W/ ASTM SPEC A653 AND BE HOT DIPPED GALVANIZED.
- ② ANCHOR SHALL BE 2.25"x2.25" OD SQUARE STEEL, MINIMUM 14 GAUGE WITH 7/16" DIE PUNCHED KNOCKOUTS ON 1" CENTER COMPLYING WITH ASTM SPEC. A653 AND BE HOT DIPPED GALVANIZED. ANCHOR SHALL HAVE MINIMUM OF 3 HOLES ABOVE GRADE.
- ③ ANCHOR SHALL HAVE TAPE INSTALLED ON BOTTOM AS WELL AS ALL SIDES TO KEEP INSIDE CLEAR OF ALL MATERIAL.
- ④ FOR IN-SIDEWALK INSTALLATIONS, CORE 4" DIA HOLE. ANCHOR LENGTH SHALL BE 12".
- ⑤ INSTALL TWO DRIVE RIVETS  
ZUMAR INDUSTRIES #TL3806 OR EQUIVALENT
- ⑥ INSTALL TWO CORNER BOLTS AND NUTS  
ZUMAR INDUSTRIES #TL070 OR EQUIVALENT

**SIGN INSTALLATION:**

SEE TRAFFIC STREET SIGN DETAIL TR-575 FOR GUIDANCE ON SIGN INSTALLATIONS.



**CITY OF EDMONDS**  
PUBLIC WORKS  
DEPARTMENT

**SIGN POST INSTALLATION  
IN SIDEWALK AREA**

APPROVED BY: **R. ENGLISH**

REVISION DATE  
**FEBRUARY 2018**

STANDARD  
DETAIL  
**TR-572**