


- * END, PULL, GATE & CORNER POSTS: 4"
- * TOP & BRACE (MID) RAIL: 1-1/4"
- * TRUSS ROD 1/2"Ø THREADED WITH TURN BUCKLES FOR ADJUSTMENT
- * TENSION WIRES REQUIRED

NOTES:

1. REQUIRED FOR CITY PROJECTS ONLY.
2. FENCE POST SHALL BE 8' ON CENTER.
3. BARBED WIRE MAY BE ADDED AS DIRECTED BY THE ENGINEER.
4. FENCE FABRIC SHALL BE SECURED TO GATE FRAMES WITH KNUCKLED SELVAGE ALONG TOP EDGE FOR CHAIN LINK FENCE INSTALLATIONS.
5. MINIMUM POST LENGTH: 9'-0" OR 7'-0" (WITH 3'-0" IN CONCRETE).
6. ALL COMPONENTS OF FENCE SHALL BE VINYL COATED-COLOR BLACK.
7. PLASTIC PRIVACY SLATS TO BE INSTALLED, WHEN APPROVED BY THE ENGINEER, & EACH SLAT WILL BE SECURED TO FENCE BY DRILLING HOLE IN BOTTOM OF SLAT & SECURING THEM TO FENCE USING ALUMINUM TWIST WIRE.
8. FOR CITY APPLICATIONS, 3 STRAND BARBED WIRE SHALL BE INSTALLED ATOP THE FENCE.



CITY OF EDMONDS
PUBLIC WORKS
DEPARTMENT

CHAIN LINK FENCE

APPROVED BY: **R. ENGLISH**

REVISION DATE
JANUARY 2018

STANDARD
DETAIL
TR-584