



DETECTABLE WARNING PATTERN AREA SHALL BE YELLOW.



	MIN.	MAX.
A	1 5/8"	2 3/8"
B	5/8"	1 1/2"
C	7/16"	3/4"
D	7/8"	1 7/16"

DETAIL B



TRACTION GRID PATTERN
TACTILE WARNING TEXTURING

DETAIL A

NOTE:

1. AT LOCATIONS WHERE NEW RAMPS ABUT EXISTING CURB, GUTTERS, PLANTER STRIPS, AND SIDEWALKS, CONSTRUCT NEW RAMPS TO MATCH ADJACENT SURFACES.
2. ALL CONCRETE SURFACES SHALL HAVE A LIGHT BROOM FINISH.
3. CONCRETE SHALL BE SPRAYED WITH A CLEAR CURING COMPOUND OR SHALL BE COVERED AND KEPT MOIST FOR 72 HOURS.
4. DETECTABLE WARNING PATTERNS (TRUNCATED DOMES) SHALL BE REQUIRED ON ALL PUBLIC STREETS WITH A CURB RETURN AND PRIVATE STREETS SERVING FIVE OR MORE LOTS. TRACTION GRID (DIAMONDS) TO BE USED AS INDICATED.
5. FOR NON-INTERSECTION CURB RAMPS ON PRIVATE PROPERTY, THE STANDARD DIAMOND PATTERN MAY BE USED AS INDICATED IN DETAIL A.

CITY INSPECTION REQUIRED ON FORM WORK PRIOR TO POUR.
ACCESSIBLE RAMP SHALL BE POURED SEPARATELY FROM CURB AND GUTTER.



CITY OF EDMONDS

REVISIONS		STANDARD DETAIL		
APPROVED BY	DATE			
D. GEBERT	03/24/05	CURB RAMP TYPE 2		
D. GEBERT	06/27/05			
D. GEBERT	04/2/07			
		DATE	SCALE	DWG NO.
		7/24/01	NTS	E2.15